

ArcGIS Desktop Tips and Tricks II

UGIC 2008 Cedar City, UT

Will start at 8:30

Jeremiah Lindemann

Outline

- Section 1
 - Geoprocessing
 - Geoprocessing Settings
 - Model Builder hints and tricks
- Section 2
 - Customizing ArcGIS Destkop
 - Customizing the UI
 - Introduction to VBA

• Q & A

Section Outline

- Geoprocessing Documentation
- Environments and Settings
 - Levels of Environments, Saving GP settings
- Managing Toolboxes
 - Where are toolboxes stored?
- History and Results
 - History toolbox, New Results tab
- Tools
 - Processing large datasets, Some useful tools, Batch processing
- Model Builder
 - Iterations, Variables, Lists, Series, Layer symbology, On-the-fly inputs

GP Documentation


- Tools Built in "quick help"
- ArcGIS Desktop Help system
 - Geoprocessing book
 - Geoprocessing Tool Reference book
- Documentation
 - What's New in ArcGIS 9.2
 - ESRI Support > Geoprocessing



Environments

Four levels:

- Application all tools
 - Tools > Options > Geoprocessing tab > Environments
- Tool Environments button
- Model all processes
 - Model Menu > Model Properties > Environments
- Model Process
 - Environments on tool dialog



Saving GP Settings


- Settings include
 - List of toolboxes
 - Environments
 - Contents of Results tab
 - Command Line variables



- Save settings to a file (XML), or to default manually
- C:\Documents and Settings\<your profile>
 \Application Data\ESRI\ArcToolbox\ArcToolbox.dat

Geoprocessing Settings

- Geoprocessing Settings:
 - Overwrite outputs automatically overwrite existing data
 - Where to create new toolboxes (change My Toolboxes location)
 - Automatically add tool output to display
 - Contents of ArcToolbox
 - History logging





Managing Toolboxes

- Where are custom toolboxes stored?
 - Folders
 - Geodatabases
 - My Toolboxes folder
- Common Question...
 - I created a New Toolbox in ArcToolbox, where is it stored?
 - C:\Documents and Settings\<your profile> \Application Data\ESRI\ArcToolbox\MyToolboxes
- Toolboxes can be saved to earlier versions (9.0/9.1)
 - Right-click the toolbox > Save As 9.0/9.1

History Toolbox

- Models of previous run geoprocessing sessions
- Toolbox automatically created in My Toolboxes
- Model Reports can be created documents everything contained in the model






Results Tab

New at 9.2

- A record of every tool you run
- Includes inputs, outputs, and messages
- Right-click opens a menu of useful items
 - Delete all outputs of a tool
 - Open the tool dialog and re-execute
 - Remove the entry
 - Drag and drop data
 - Copy data (text)
- Results are per application session



Processing Large Datasets

- Large inputs are tiled, processed and then reassembled
 - Messages indicate when tiling occurs
- Tools will work with the amount of memory on the machine
- Outputs should be written to file or enterprise geodatabases due to size limitations



Batch Processing

Street

New at 9.2

 Any tool may be opened in a batch mode

Right-click a tool and click Batch –
 opens the Batch grid

 Use Fill and Browse to quickly fill the batch grid

> TEXT TEXT TEXT TEXT TEXT LONG


Field Precision

Ar	cToolbox						- 6
	: : 2						
	🕀 🥎 Database						^
	🕀 🗞 Disconnected Editing						
	🕀 🔕 Distributed Geodatabase						
	Domains Feature Class						
- 11							
ш							
ш	_						
ш	/	Add Field					
ш	· · · · · · · · · · · · · · · · · · ·	Assign D	0	pen			
-		Calculate					
	·	Culculate	Ē	atch			
-	.	Delete Fi	E/	dit			
-			_	210777			
	Transpos ⊕ 🍣 File Geodatal 🖺 ⊆ору						
1							
-				elete			
ш	🛨 🥎 Generalizatio						
		davac		ename			
th	Field Alias	Field IsNu true	illable	false	Field Isl		
		NON NULLAE	H F	false		I	
		true		false		57	
		true		false			_
		true		false		4	
		true		false			_
		true		false			

Model Builder: Iterations

New at 9.2


- Iteration controls number of times a model runs
 - Fixed number of times
 - Variable value
 - Boolean condition
- Set from Model Properties




Model Builder: Variables

New at 9.2


- Setting variables for multiple outputs
 - Output from an iteration
 - In-line variables and substitution
 - %i% = current position in a list variable
 - %n% = current model iteration
 - Initial value is zero






Model Builder: Lists

- New at 9.2
- Lists are INDEPENDENT of Model Iteration
 - A process is executed for each value in a list
 - The number of outputs is equal to the maximum number of inputs
 - If input lists are not the same length, the last value is reused in the shorter list
 - The keyword %i% indicates the current list index




Model Builder: Series

- New at 9.2
- Series are DEPENDENT on Model Iteration
 - Model iteration executes the entire model each time
 - The model iteration determines which value from a series was used
 - The keyword %n% indicates the current iteration number




Model Builder: Layer Symbology

- New at 9.2
- Specify output layer symbology from existing layer in TOC or layer file (.lyr)
- The layer symbology is imported into the model and the layer or layer file are no longer referenced
- Great for re-running a model and comparing results (e.g. Weighted Overlay tool)




Model Builder: On-the-fly Inputs

- New at 9.2
- Must be used in ArcMap
- Draw features on-the-fly as inputs to the model
- Uses "feature sets" as the input Data Type
- Schema and symbology imported




Additional Reading

- Getting to Know ArcGIS Desktop, Second Edition
 - Basics of ArcView, ArcEditor, and ArcInfo, Now includes ArcGIS 9.2 trial software on DVD



- The ESRI Guide to GIS Analysis, Volume 1
 - Focuses on studying Geographic patterns and relationships



Instructor-Led Training

- Advanced Analysis with ArcGIS
 - What is spatial analysis? Geoprocessing, ModelBuilder,
 Spatial Statistics
- Introduction to Geoprocessing Scripts Using Python
 - Geoprocessing framework, basics of Python, tools and environment settings, Geoprocessor object, describe objects, cursor objects, scripts in the Geoprocessing framework
- Writing Advanced Geoprocessing Scripts Using Python
 - Manipulate strings, lists and dictionaries, read and write text files, create reusable code, read and write geometries, incorporate Python scripts into models

Outline

- Section 1
 - Geoprocessing
 - Geoprocessing Settings
 - Model Builder hints and tricks
- Section 2
 - Customizing ArcGIS Destkop
 - Customizing the UI
 - Introduction to VBA

• Q & A


Section Outline

- The VBA environment
 - Customize Dialog Box
 - Visual Basic Editor
- Creating UIControls
- Brief intro to ArcObjects
 - Common ArcObjects
 - Where to start
 - Interfaces

• Q & A


VBA Customization

- Use VBA to extend ArcMap/ArcCatalog
- Create custom user forms, buttons and tools
- Automate workflows
- Subject of this seminar



VBA development environment


- Customize dialog box
 - Customize ArcGIS interface without code
 - Create new toolbars
 - Add and remove controls
- VBA Editor
 - Code UIControls
 - Create forms
 - Write macros



Customize


ArcGIS commands

- Toolbars and menus contain commands
- Commands are buttons, menus, macros, and UIControls
- Each command has associated code




Customize dialog box

- Turn toolbars on/off and create new toolbars
- Add commands to toolbars or menus
- Password protect customizations




Customize dialog box: additional options



Creating macros

- Code written ahead of time
 - Public level Sub procedure with no arguments
- No associated button or tool
 - Must run from VBA or ArcMap menu
- Scope determines accessibility
- Add to ArcGIS interface



Setting UlControl properties

Set properties that define appearance of UIControls

- Name

– Image (16x16 bitmap)

Display text, image, or both

Begin a group


View source to write code

Opens Visual Basic Editor

Can only view code for UIControls


VBA code samples available

Customize dialog box must be open




Creating UlControls

- User-interface controls
- UIControls category
- Four types
 - Button
 - Tool
 - Edit box
 - Combo box
- Controls have events
 - UIButton: Click
 - UITool: MouseDown



Customizing ArcToolbox

- Can add and remove toolboxes
- Add tools to custom toolboxes
- Save settings to a file




Demonstration


- Examine the customize dialog box
- Start customizing the interface
 - Add a new toolbar
 - Add new buttons
 - Change icons

VBA Development Environment

- Similar environment for all applications that use VBA
 - Customize dialog box: Interface customization
 - Visual Basic Editor: Write code




Visual Basic Editor



Accessing your customizations


- ArcMap has three levels of storage
- Templates read in order on startup



- Changes to ThisDocument override templates
- ArcCatalog only uses Normal.gxt template


Modules

- Documents that store code
 - Module (standard module): Contains standalone code
 - Class module: Contains a class definition
 - UserForm: Contains code and layout for a form




UIControls

- User created commands
- Four types
 - Button
 - Tool
 - EditBox
 - ComboBox




Event Procedures



Navigating Event Procedures

- Choose a control in the Object box
- Choose an event in the Procedure box



Demonstration


- Create a UI control with the Customize Dialog Box
- Display a simple Message Box upon click

ArcObjects


- The building blocks of ESRI software
 - ArcGIS Desktop
 - ArcGIS Engine
 - ArcGIS Server

Common ArcObjects

ArcGIS is built with a set of ArcObjects



Common ArcObjects




Object Oriented programming

- Object members:
 - •Properties (■—■)
 - Methods (←)

Map ArcObject


- **--**Layer: ILayer
- --- LayerCount: Double
- -- Name: String
- --- Reference Scale: Double
- --- SelectionCount: Double
- ← AddLayer(ILayer)
- **←** ClearLayers
- **Extent:** IEnvelope
- **= - FullExtent: IEnvelope**
- --- GraphicsContainer: IGraphicsContainer
- -- Selection: ISelection
- **←**Clear
- **←**Refresh

Interfaces




Relationship between ArcObjects

- To reference an existing ArcObjects
 - Can not reference it directly
 - Must think about where it resides in object model




Starting points for writing code


- VBA offers two preset variables
 - Application references the ArcMap application
 - ThisDocument references the MxDocument



ArcObjects example



Finding Existing Code




- Use VBA Help
 - Tips 🧌
 - Source code
 - Copy and paste into VBA
- http://edn.esri.com
 - Code Exchange tab

Demonstration

- Examine the VBA Developer Help
- Copy a code snippet to work with ArcMap

Useful Resources

- ESRI Developer Network (EDN):
 - http://edn.esri.com/
 - Documentation
 - Samples
 - Discussion forums
- Instructor led training
 - http://training.esri.com
- Book: Getting to Know ArcObjects



Open to Questions

• Thanks for attending!